

OPEN POSSIBILITIES.

Introducing advanced cooling
solutions into existing data centers



NOVEMBER 9-10, 2021

Introducing advanced cooling solutions into existing data centers

Design considerations and, operational and performance learnings

Yueming Li, Thermal Engineer, Meta
Kiran Somanchi, Program Manager, CoolIT Systems
Dennis Trieu, Mechanical Engineer, Microsoft

OPEN POSSIBILITIES.



Driving Factors



Component power and density pushing limits of air-cooling.



AALC is an enabling technology. Facility water integration may not be as rapid as component power/cooling trends.



Lower cost solution to retrofitting air-cooled data centers with facility water.




Higher efficiency than air cooling for similar power density.

OPEN POSSIBILITIES.

Stretching Limits of Air Cooling

Extends life of air-cooled facilities and adds optionality for DC owners



OPEN POSSIBILITIES.




Rack-level Deployment Approaches




ADVANCED
COOLING
FACILITIES

Door Heat Exchanger



Side Car Heat Exchanger



OPEN POSSIBILITIES.

Why two solutions?



Door Heat Exchanger

Pros

- Compact and self-contained
- Squeeze more racks into data center
- Common air flow for IT and door HX

Cons

- 4U space lost to RPU
- Lower cooling capacity than side car
- Custom mounting brackets maybe needed

Side Car Heat Exchanger

Pros

- Higher cooling capacity
- Easier to deploy – rack and roll
- Rack space for additional blades not

Cons

- Side car takes up room

OPEN POSSIBILITIES.



OPEN POSSIBILITIES.

Operational Learnings



NOVEMBER 9-10, 2021

RDHx Challenges (Rear-door)

Category	Learning	Challenge
System assembly	RDHx is heavy, should be designed with assembly in mind.	With a mass of < 150 kg (filled), should not be installed without mechanical aid
Characterization	Server fans need to produce a certain amount of pressure or fans need to communicate with RDHx to set cooling requirements	Each server and fan profile will affect characterization
Serviceability	Challenging with mass and accessing hot aisle	Field replacement of RDHx
Maintenance	Opening rear door for maintenance reduces cooling capacity for rack	

OPEN POSSIBILITIES.

RDHx Learning (Rear-door)



ADVANCED
COOLING
FACILITIES



Once assembled, can handle up to 24kW with an OTS RDHx. Optimized can hit > 40kW



Efficient utilization of floor space



Enables higher density servers and higher TDP chips.



All airflow that moves through the servers goes through the HEX

OPEN POSSIBILITIES.



Adjacent Rack HEX Challenges



ADVANCED
COOLING
FACILITIES

Category	Learnings
System assembly	Designed to work with ORv3 rack and power. Optimized solution could be built without these constraints.
Characterization	Adequate airflow management / balancing between IT gear and cooling racks.
Serviceability	Easier to service in the field
Maintenance	Actions on either rack should not have influence on the other rack

OPEN POSSIBILITIES.



Adjacent Rack Learning



ADVANCED
COOLING
FACILITIES



Easy to rack and roll



Requires no changes to the IT rack for cooling



Can support multiple racks of IT gear



Achieved higher than expected performance

OPEN POSSIBILITIES.

Future steps for qualifying AALC



System integrator review to deploy at scale



Adequate airflow management / balancing between IT gear and cooling racks



Performance / efficiency optimization to hit 40kW cooling

OPEN POSSIBILITIES.



RPU Spec Overview



OCP
GLOBAL
SUMMIT

NOVEMBER 9-10, 2021

Why of the spec



STANDARDIZATION
AND CONSISTENCY



INTEROPERABILITY
BETWEEN VENDORS



WIDER ADOPTION AND
BETTER ECOSYSTEM

OPEN POSSIBILITIES.

OCP Specification Outline



1. Scope
2. Terminology
3. Overview
4. RPU Requirements
 - Physical, Performances, Monitoring, and Operational
5. Sensor Requirements
 - Sensor List, Control Scheme, Alarms and Field Safety
6. Environmental Conditions
7. Serviceability and Operational Impact
 - Touch points, Pump, Filtration, Loading Force, LED Standard
8. Compliance and Safety
 - ESD, Flame Rating, Noise, Vibe & Shock
9. Test Requirements
 - Leaks, Functional Testing and Calibration, Burn-in, Test-to-Failure
10. Long-term Reliability

OPEN POSSIBILITIES.



OCP Specification Preview



4RU chassis designed to fit in 19" rack

Adapter frame for Open Rack V2 and V3

DC and AC input variants

N+1 redundancy for all moving parts is a must

Consumes $\leq 5\%$ of rack IT power (including liquid-to air HX)

Controls and monitors the liquid-to-air HX

Standardized controls and reporting interface for rack level / DCIM



OPEN POSSIBILITIES.





Photos of Prototype Builds

CoolIT RPU



Delta RPU



OPEN POSSIBILITIES.

Photos of Prototype Builds

CoolIT hot-swappable pump RPU



OPEN POSSIBILITIES.




Prototype Implementations




ADVANCED
COOLING
FACILITIES

RPU + RDHx



Reservoir and Pumping Unit

Adjacent Side Car Hx



OPEN POSSIBILITIES.

Next Steps for Working Committee



ADVANCED
COOLING
FACILITIES



Signed final spec agreement for RPU



Incubation committee submission and approval



Side-car and RDHx specs

OPEN POSSIBILITIES.





ADVANCED
COOLING
FACILITIES

Join the mailing lists:

Advanced Cooling Solution: <https://ocp-all.groups.io/g/OCP-ACS>

Door Heat Exchanger: <https://ocp-all.groups.io/g/OCP-ACS-Door-Heat-Exchanger>

Cold Plate Work Stream: <https://ocp-all.groups.io/g/OCP-ACS-Cold-Plate>

Immersion Work Stream: <https://ocp-all.groups.io/g/OCP-ACS-Immersion-Cooling>

Project Wikis:

[Rack & Power](#)

[ACS Door HX](#)

[ACS Cold Plate](#)

[ACS Immersion](#)

OPEN POSSIBILITIES.



Open Discussion



OCP
GLOBAL
SUMMIT

NOVEMBER 9-10, 2021